

# #9615 super bond tape

FilmLOC's super bond woven polypropylene repair tape

## Description

High strength reinforced woven PP tape with an extremely aggressive adhesive. Repair tape for patching Super Sack® containers, bulk bags, FIBC's, bales, woven fabric and tarps; for strapping and banding of various types of products that require extra strength; for seaming carpet backings for industrial and consumer use and for other industrial applications. Exceptional for use in applications that require extra strength and an aggressive adhesive. Easy to apply and approved for indirect food contact by FDA regulation title 21, subpart B, section 175.105. Can be sewn. Manufactured in the USA.

## Product Data

Film	Reinforced PP woven cloth
Adhesive	Hot melt synthetic rubber adhesive
Liner	60# poly-silicone release liner
Overall Thickness	2.2 mil (+/- 5%)
Peel Adhesion	130 ounces per inch width
Tensile Strength	24.3 pounds per inch
Application Temperatures	60 degrees F - 110 degrees F
Operating Temperatures	0 degrees F - 110 degrees F
Recommended Storage	Temperature 72 degrees F + 50% humidity
Shelf Life	One year at recommended storage levels

## Ordering Information

Colors	Natural
Stock Sizes	4' x 36 yd. - 12 rolls per case 6' x 36 yd. - 8 rolls per case 8' x 36 yd. - 4 rolls per case
Minimum Order	1 case
Custom Sizes	Other sizes available. Minimum quantities apply.



**FILMLOC**.com  
p\_800.783.6258 p\_404.892.8778 e\_info@filmloc.com